

Datasheet of **Kamero**

Product Name	LED Post-Top Light
Product SKU	ML-KMR-60W453525-CCT
Product Characteristics	<ul style="list-style-type: none"> <li>● Both of CCT&amp;Power selectable for different application.</li> <li>● Lumileds SMD2835 with high efficiency up to 150lm/w</li> <li>● SOSEN higher-class NH-E driver, 100~277Vac, PF0.95, Surge 6kV</li> <li>● Improved new housing tooling with better heat dissipation.</li> <li>● Improved cover-fixing solution, built with dip-switch outside, more convenient for operation.</li> <li>● Available with frosted PC cover to reduce the UGR value.</li> <li>● Available with beam angle TYPE II, TYPE III, 60°, 90°</li> <li>● IP66 and IK09 protection.</li> <li>● Built-in with NEMA socket, Daylight sensor available.</li> <li>● SUS316 screws with better corrosion protection.</li> <li>● Complied by CE/ENEC/RoHS/ErP2.0/SAA</li> <li>● Rated life span 50,000hrs@L80B20@25 °C</li> <li>● 5 years warranty.</li> </ul>
Application	Industrial, Commercial



Product Specification

Model no.	ML-KMR-60W453525-CCT
Power	60W/45W/35W/25W
LEDs	<b>Lumileds SMD2835</b>
Colour	5000K+4000K+3000K
Effective Lumen	8400lm/ 6300lm/ 4900lm/ 3500lm
Colour Rendering Index	RA≥70
Beam Angle	TYPE II (64*155°), TYPE III (60*155°), TYPE IV (60*150°), 60°,90°
Driver	<b>SOSEN, NH-E series</b>
Power Factor	0,95PF
Surge Protection	L-N: 6kV, L/N-PE: 6kV
Input Voltage	AC100~277V
Input Frequency	50/60Hz
Operating Temperature	-30°C ~50°C
Dimmable	Non-dimmable, 1-10V dim optional
Lifespan	50,000hrs@L80B20@25 °C
Warranty	5 Year
Ingress Protection Rating	IP66
Battery Backup	Available on request
Main Materials	Aluminium / Polycarbonate
Screws	SUS316 screws
Pole Size	66mm(60~70mm), 5mm Pole Sleeve Thickness
Certifications	IEC / LOA / CE / ROHS
Dimension	D404*H518mm



Comments..... Project.....